

Fig. 5973, 5973G Cast Iron Metrex Commissioning Sets Chilled Water, LTHW & MTHW

FEATURES AND BENEFITS

- Robust iron body materials for long service life
- Precise flow regulation and accurate measurement
- Flanged with handwheel – easy to install and operate
- Positive flow control at all handwheel settings



MATERIAL SPECIFICATION

Component	Material	Specification	
		BS EN	ASTM
Valve	Fig. 973 (see page 41 for materials)		
Test Points	Fig. 631		
Extension Sleeve	Bronze	1982 CC491K	B62
Housing	Cast Iron	1561 EN-JL1040	A126 Cl B
Orifice Plate	Stainless Steel	10088-1 XCrNiMo 17-12-2	AISI 316

PRESSURE/TEMPERATURE RATING

EPDM Seat
16 bar from -10 to 120°C

SERVICE RATING

Suitable for Chilled Water, LTHW and MTHW

TEST PRESSURES (HYDRAULIC)


Shell: 24 bar
Seat: 17.6 bar

SPECIFICATION

A close coupled commissioning set comprising a lugged butterfly valve and metering station to offer all the advantages of the close coupled concept together with an accuracy of $\pm 5\%$ of flow rate. Gear operation provides infinitely variable settings between fully open and closed positions. The commissioning set is supplied as a single unit.


Supplied complete with figure 631 test points and necessary bolting for connection of the valve end to the system. Comprehensive flow charts available. Note: The valve should be not less than 30° open for regulation duties. Wrench operated version available in sizes 50 to 200mm. Figure 9973G available, stainless steel disc.

DIMENSIONAL DRAWINGS



DIMENSIONS AND WEIGHTS

Nom Size	mm	50	65	80	100	125	150	200	250	300
A	mm	133	151	166	192	221	246	300	358	418
B	mm	135	145	160	165	180	190	225	255	275
H	mm	182	190	197	219	232	254	278	281	306
J	mm	123	123	123	123	123	123	123	228	228
K dia	mm	125	125	125	125	125	125	125	300	300
Weight (geared) kg		13	15	21	26	33	45	69	94	131



For Commissioning Valve Coefficients please refer to pages 49-51.

Every effort has been made to ensure that the information contained in this publication is accurate at the time of publishing. Hattersley Ltd assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.